

Tracking Systems and Applications

Stephen M. Lichten
Manager, Tracking Systems and Applications Section
818-354-1614
Stephen.Lichten@jpl.nasa.gov

James Zumberge
Deputy Manager, Tracking Systems and Applications Section
James.F.Zumberge@jpl.nasa.gov

Both at: Jet Propulsion Laboratory
Mail Code 238-638A
4800 Oak Grove Dr.
Pasadena, CA 91101

Jet Propulsion Laboratory, California Institute of Technology





JPL's Tracking Systems and Applications Section (335)



- **Technologies for precision spacecraft tracking, remote sensing, and science**
 - GPS and spacecraft-spacecraft tracking systems technologies
 - Frequency and timing: advanced atomic clocks; oscillators and resonators
 - Quantum sciences and technologies
 - Radio interferometry, antenna arraying, and correlators
 - Earth and planetary science, astronomy, fundamental physics
- **Sponsors: NASA, USAF, Navy, NRO, FAA, commercial partners**
- **Our Section is one of five in JPL's Telecommunications Science and Engineering Division**
 - 128 employees (11 technical groups), 108 with B.S. or higher (74 Ph.D.'s)
 - 5 groups focused on GPS technology (two hardware and three analysis groups)
 - 2 groups focused on Frequency/Timing systems and quantum technologies
 - 3 groups focused on RF and optical interferometry
 - 1 group focused on solid Earth, atmospheric, and ocean science



Introduction (cont.)

- **Diverse section with technologists, specialists, and scientists provides a “cradle to grave” capability in GPS-based systems and applications**
 - Signal structure expertise; in-receiver algorithms and software; performance trades
 - Innovative GPS receiver design
 - Numerous spaceborne experiments and deployments
 - Orbit/trajectory estimation and user positioning algorithms & software
 - Precise spacecraft-spacecraft tracking systems
 - GPS global ground networks and automated data acquisition systems for precision ground and orbiting applications (operating on 24/7 basis)
 - Real-time and non-real-time applications; navigation/positioning; geolocation and time transfer; tropospheric and ionospheric science; gravity science; geophysics
- **Frequency and Timing unique core expertise**
 - Responsible for 24/7 operation of mission critical NASA/JPL frequency and timing subsystems in global Deep Space Network
 - Advanced atomic clock technology development; innovative oscillators and resonators; precision time and frequency measurements for NASA, USAF Research Lab and USNO
 - Underlying fields: quantum optics and electronics, laser cooling, fundamental physics
 - Presently building advanced space clocks for future GPS (Linear Ion Trap clock) and Space Station (Laser cooled clocks) deployments




Advanced GPS Receiver Technology (a)




TurboRogue
Commercial
Ground Receiver
(1992)

GPS/MET
Class
Ruggedized
A/D Converter
RS-422
(1995)

Ørsted Class
Low Power
Data Compression
(1996)



Bit-Grabber Class
Ultra-Low Power Nav
RF Sampling @
LEO/GEO
CA/PY Ground Proc.






Advanced GPS Flight Receivers/Transceivers (b)



SAC-C Class

Hi- Performance
PowerPC
CPU
Lower Power
Multi-Antenna




Raptor Class

Additional Functions
Lower Power

And

ST5
COSMIC 8 sats 1/03
LCAP, PARCS






Precision LEO Positioning and Timing



- GPS tracking maintains constant and precise knowledge of relative spacecraft positions & clocks






Demonstrated Orbit Accuracies With GPS




Geostationary
36000 km altitude
(TDRS, INMARSAT)

15 m
ground-based tracking



GPS
20000 km
altitude


8 cm (< 40-cm real-time)
operational automated processing



MicroLab/GPSMET
730 km altitude

With GPS < 10 cm

TOPEX/POSEIDON




1336 km altitude


With GPS: < 2 cm radial accuracy
operational automated processing

Recent (2000) JPL Blackjack Flight GPS Receiver Results

Shuttle Radar Topography
Mission (SRTM): 230-km alt
45-cm orbit accuracy



CHAMP: 470-km alt
< 10-cm orbit accuracy




SAC-C: 705-km alt
< 10-cm orbit accuracy

FUTURE GOAL: < 1-cm Orbit
Accuracy for LEOs



Ultra-Precise Time Transfer with GPS




Linear fits to GPS-based clock estimates for pairs of masers worldwide (some separated by 1000's of km) show rms scatter of better than 30 picosec

FOR OFFICIAL GOVERNMENT USE ONLY: PROPRIETARY DATA - JPL/AEROSPACE MOU


Aerospace Corp. Briefing: S.Lichten July 2001

- GPS and/or LEO cross-link tracking maintain constant and precise knowledge of relative spacecraft positions & clocks







JPL Spacecraft Cross-Link Sensors Under Development for Space Deployments in 2001-2005




GRACE: JPL GPS Receiver with integrated camera and K-band spacecraft-spacecraft tracking, to provide 1-micron accuracy measurement of range change to improve knowledge of the Earth's gravity field by several orders of magnitude



Starlight: Precision (1-cm) formation flying



Mars Network Node: Integrated Navigation and Telecommunications





ST-5: GPS-based Constellation Communications and Navigation Transceiver (CCNT) for cross-link ranging and inter-spacecraft telecom in constellation of spacecraft in GEO-transfer elliptical Earth orbit



Global Positioning System (GPS) Measurements Applied to Geophysics and Natural Hazards




- NASA contributes about one-quarter of the > 200 GPS tracking stations in the International GPS Service (IGS) global network
- Analyses of their data is interpreted in terms of tectonic plate motions and geodynamics
- High density deployment of GPS sites contributes to the assessment of earthquake hazards (southern California map)




IGS Global Network

Novel Science Applications



Atmospheric and Ionospheric Remote Sensing and Science




Bi-Static Ocean Reflectometry



California Institute of Technology

Task: GPS Wide Area Augmentation System (WAAS) Implementation




Task Purpose/Objectives:

- Deliver real-time software prototype to DOT/FAA for new GPS-based precision navigation system (WAAS) for aviation.

Major Products and Deliverables:

- Real-time software for GPS orbits, clocks, and ionosphere maps
- New GPS and safety algorithms



Customer Relevance:

- Improve airline navigation accuracy by orders of magnitude; enhance aviation safety in U.S.
- Save \$12B+ in next decade in fuel and airport costs

NASA Relevance:

- Real-time, autonomous space navigation
- Onboard science data product generation
- Real-time natural hazard monitoring
- Pathfinder for the Mars Network Infrastructure.

FOR OFFICIAL GOVERNMENT USE ONLY: PROPRIETARY DATA - JPL/AEROSPACE MOU

Aerospace Corp. Briefing: S.Lichten July 2001




Ionospheric Research At JPL



10/22/99
22:00 - 22:15 UT

Ionospheric TEC



Goal: Mitigate impact of ionosphere on COMM, NAV and SURVEILLANCE systems

Capabilities:

- Accurately characterize ionospheric behavior
- Real-time input/output
- Tailored products

Technical Expertise:

- Global snapshots of TEC in near real-time
- Data analysis for space-borne GPS receivers
 - Vertical electron density profiles & tomography
 - CHAMP, SAC-C & GRACE missions in FY'02
- Advanced global modeling development (GAIM)
 - Broad range of outputs (e^- density, winds, etc.)
 - Broad range of inputs (TEC, UV images, etc.)
- GPS Global Network
 - Real-time processing
 - Scintillation monitoring

Possible Joint Developments:

- Near real-time prediction of Total Electron Content
 - Accuracy study by Aerospace Corp.
 - Tailored development to further boost performance
- Joint analysis of space-borne GPS data
 - IOX instrument on PicoSat (L. 9/2001)
 - CORISS instrument on C/NOFS (L. 2003)
- Scintillation monitoring and prediction
- Improved global electron density specification
 - Tailor GAIM towards applications of interest
 - Accommodate new data types
- Transfer software

FOR OFFICIAL GOVERNMENT USE ONLY: PROPRIETARY DATA - JPL/AEROSPACE MOU


Aerospace Corp. Briefing: S.Lichten July 2001



Precise Real-Time Global GPS Navigation



- Established a global, real-time, GPS ground network
 - Real-time user accuracies: 8 cms RMS horizontal, 20 cms RMS
 - ~ 10 times better than best available commercial and military systems
 - 30-40 cms 3D (RSS) global GPS orbits, in real-time
 - Winner of the 2000 NASA Software of the Year Award!
 - JPL's initial implementation utilizes Internet for communications; the system is being commercialized by Navcom who is adding GEOs to the network
 - NASA, DoD and commercial applications being studied, including:
 - RLV navigation
 - Automated LEO navigation and onboard science data product generation



AOA Benchmarks




Turbo-Rogues



Ashtech Z-12s



JPL's New Global Capability Supports 10-20 cm User Accuracy, Anywhere, Real-Time



**Revolutionary new capability:
decimeter real time positioning, anywhere, anytime**

Capability		JPL's IG DG	Un-augmented GPS	Others (WADGPS services)
Coverage:	Global	Yes	Yes	No
	Seamless	Yes	Yes	No
	Usable in space	Yes	Yes	No
Accuracy:	Kinematic applications	0.1 m horizontal 0.2 m vertical	5 m	> 1 m
	Orbit determination	0.01 – 0.05 m (goal)	1 m	N/A
Dissemination method		Internet/broadcast	Broadcast	Broadcast
Targeted users		Dual-frequency	Dual-frequency	Single-freq.





Remote user running IGDG

For more info:
<http://gipsy.jpl.nasa.gov/igdg>










Frequency, Timing and Quantum Sciences and Technologies

Responsible for technology development, generation, and distribution of ultra-stable reference frequencies and synchronized timing signals for NASA's Deep Space Network (DSN).




Major research and technology development:

- Linear Ion Trap Standards (LITS)
- *GPS LITS: Space version of LITS*
- Cryogenic Sapphire oscillators (CSO)
- Stabilized Optical Fiber microwave link (FODA)
- *Opto-Electronic Oscillator (OEO)*
- Micro spheres
- Trapped single ion experiment
- Laser Cooling and Atomic Physics (LCAP)
- *Space clocks - Primary Atomic Clock in Space (PARCS), Rubidium Atomic Clock Experiment (RACE)*
- *Bose-Einstein Condensate (BEC) generation*
- *Quantum Interferometer Gravity Gradiometer (QUIGG)*



- Developed Low Rate (<250 sym/sec) Telemetry system arraying up to 7 antennas, for the Galileo Mission
- Completing a follow-on High Rate (6 Mega-sym/sec) Telemetry system arraying up to 8 antennas, for DSN
- Developed prototype Ka Band Array Feed and Signal Processing system for DSN 70m antenna enhancement
- VLBI (Very Long Baseline Interferometry) Correlators
 - Developed a narrowband (250 kHz) system in both H/W and later in S/W, primarily for spacecraft navigation
 - Developed a wideband (28-channel, 4 MHz, 4 station) H/W system used for Geodesy, Astrometry, Astronomy
 - Developed a real-time wideband (14-channel, 4 MHz, 2 station) correlator of same design as above system, together with a 800 Mbit/sec fiber optic channel for interconnecting antennas
 - Are in process of implementing a replacement wideband (16-channel, 16 MHz, 4 station) H/W system to be used for Space VLBI in addition to the above applications.
 - Developing a real-time wideband (8-channel, 16 MHz, 2 station) correlator of same design as above, with a 1 Gbit/sec fiber optic channel, to replace the above real-time system.



Advanced Microwave Sensing (Interferometric Imaging from Space)

- **JPL/Section 335 participated in study of advanced interferometric imaging capabilities from space platforms**
 - Sponsored by NRL Code 7214 and another DoD organization
- **Examined feasibility & assessed technical issues for such systems**

• Study Goals


- Covertly detect, characterize, locate, and track all man-made earth-based and air-borne sources of RF energy and communications
- Monitor & map all natural sources of RF energy and changes to them due to natural and human activities
- Provide 24/7 day/night, all weather surveillance capability, precise geolocation, & penetration

• Overview & Program Planning

- Develop concept arrays for detection and characterization of possible targets
- Different array architectures were evaluated for performance, costs, and operational issues
- Technology issues and tradeoffs were defined

• Issues Affecting Space Operations

- A number of issues were investigated for orbit and cluster configurations, antenna and receiver designs, and communications and on-board data processing/compression





Selected References

Ionospheric electron density profiles obtained with the global positioning system: Results from the GPS/MET experiment, Hajj GA, Romans LJ, Radio Science v33: (1), 175-190, JAN-FEB, 1998

A global mapping technique for GPS-derived ionospheric total electron content measurements, Mannucci AJ, Wilson BD, Yuan DN, Ho CM, Lindqwister UJ, Runge TF Radio Science v33, (3), pp 565-582, 1998

Monitoring of global ionospheric irregularities using the worldwide GPS network, Pi X, Mannucci AJ, Lindqwister UJ, Ho CM, Geophysical Research Letters v24, 18, pp 2283-2286, 1997

COSMIC: GPS ionospheric sensing and space weather, Hajj GA, Lee LC, Pi XQ, Romans LJ, Schreiner WS, Straus PR, Wang CM, Terrestrial Atmospheric And Oceanic Sciences v11: (1), 235-272, MAR 2000

Imaging the Ionosphere With The Global Positioning System, Hajj GA, Ibanez-Meier R, Kursinski ER, Romans LJ, International Journal Of Imaging Systems And Technology v5: (2), 174, Summer, 1994

Ionospheric total electron content perturbations monitored by the GPS global network during two northern hemisphere winter storms, Ho CM, Mannucci AJ, Sparks L, Pi X, Lindqwister UJ, Wilson BD, Iijima BA, Reyes MJ, Journal Of Geophysical Research-Space Physics, v103, (A11), pp 26409-26420, 1998

microGPS: On-Orbit Demonstration of a New Approach to GPS for Space Applications, J. Srinivasan, Y. Bar-Sever, W. Bertiger, S. Lichten, R. Muellerschoen, T. Munson, D. Spitzmesser, J. Tien, S. Wu, and L. Young, Navigation, Vol. 47, Number 2, Summer 2000, pp. 121-127.

NASA's Global DGPS for High-Precision Users, R. Muellerschoen, Y. Bar-Sever, W. Bertiger, and D. Stowers, GPS World, January 2001, Vol. 12, Number 1, pp. 14-20.

Results of an Internet-Based Dual-Frequency Global Differential GPS System, Muellerschoen, R.J., W. I. Bertiger, M. F. Lough. ION Meeting, San Diego, California, June, 2000.

GPS Precise Tracking Of Topex/Poseidon: Results and Implications, Bertiger, W. I., Y. E. Bar-Sever, E. J. Christensen, E. S. Davis, J. R. Guinn, B. J. Haines, R. W. Ibanez-Meier, J. R. Jee, S. M. Lichten, W. G. Melbourne, R. J. Muellerschoen, T. N. Munson, Y. Vigue, S. C. Wu, and T. P. Yunck, B. E. Schutz, P. A. M. Abusali, H. J. Rim, M. M. Watkins, and P. Willis, JGR Oceans Topex/Poseidon Special Issue, Vol. 99, 1994, pp. 24449-24464.